



Rougier Afrique International

Managing forests. Enriching wood.



APPLICATIONS:

- Construction caravan components
- Shop fittings
- Carpentry
- Paper overlay

ILOMBA TWIN-PLY

Ilomba TWIN-ply is produced with selected Ilomba face veneers resulting in a very smooth surface

GENERAL INFORMATION

Faces	BB/BB (III/III) as per EN 635-2 Ilomba (<i>Pycnanthus angolensis</i>)
Finish	Calibrated and both sides sanded
Glue	Class 3 phenolic EN 314-2 E1/2 EN717-1
Formaldehyde emission	(EN 717-1): < 0.01 mg/m ³ (test conducted on 16 April 2026)
Density	± 500 kg/m ³ (+/- 10%) according EN 323
Dimensional tolerance	according EN 315
Sustainability certification	FSC® 100% (certificate FSC® C143628,CU-COC- 874178) on demand
Legality	EUTR and EUDR compliant CE for non-structural use according EN 13986

Thickness	2500x1220 mm		3100x1300 mm	
	plies	pcs/crate	plies	pcs/crate
8 mm	5-ply		5-ply	
10 mm	5-ply		5-ply	
12 mm	7-ply		7-ply	
15 mm	7-ply		7-ply	
18 mm	9-ply		9-ply	



The given information in this datasheet is non-binding and can be changed without prior notice.