



Rougier Afrique International

Managing forests. Enriching wood.



APPLICATIONS:

- Curved furniture
- Caravans
- Carpentry

OKOUGREEN FLEX

Okougreen Flex is produced with selected 100% Okoume veneers and designed for maximum flexibility

GENERAL INFORMATION

Species	100% Okoume (Aucoumea klaineana)
Faces	B/BB (II/III) as per EN 635-2
Finish	Calibrated and both sides sanded
Glue	Class 3 phenolic EN 314-2 E1/2 EN717-1
Formaldehyde emission	(EN 717-1): < 0.01 mg/m ³ (test conducted on 16 April 2026)
Density	480-500 kg/m ³ (+/- 10%) according EN 323
Dimensional tolerance	according EN 315
Sustainability certification	FSC® 100% (certificate FSC® C143628, CU-COC-874178) on demand
Legality	EUTR and EUDR compliant CE for non-structural use according EN 13986

Thickness	2500x1220 mm			1220x2500 mm		
	plies	radius	pcs/crate	plies	radius	pcs/crate
3 mm	3-ply			3-ply		
4 mm	3-ply			3-ply		
5 mm	3-ply			3-ply		
5,5 mm	3-ply			3-ply		
6 mm	3-ply			3-ply		



The given information in this datasheet is non-binding and can be changed without prior notice