



Rougier Afrique International

Managing forests. Enriching wood.



OKOUGREEN PRESTIGE

Okougreen Prestige is produced with carefully selected 100% Okoume veneers for high demanding exterior applications under KOMO® certified



APPLICATIONS:

- Exterior wall cladding
- Garage and front doors
- Balcony shutters
- Construction in extreme outdoor environment

GENERAL INFORMATION

Species	100% Okoume (Aucoumea klaineana)
Faces	B/BB (II/III) as per EN 635-2
Core	selected veneers (KOMO®) selected 100% natural full sheets (Prestigio)
Finish	Calibrated and both sides sanded
Glue	Class 3 phenolic EN 314-2 E1/2 EN717-1
Formaldehyde emission	(EN 717-1): < 0.01 mg/m ³ (test conducted on 16 April 2026)
Density	480-500 kg/m ³ (+/- 10%) according EN 323
Dimensional tolerance	according EN 315
Technical certification	KOMO® (certificate 21100) on demand.
Sustainability certification	FSC® 100% (certificate FSC® C143628 ,CU-COC-874178) on demand
Legality	EUTR and EUDR compliant
Marking	CE2+ for structural use ≥ 8 mm according to EN 13986 CE for non-structural use < 8 mm according to EN 13986

	2500x1220 mm		3100x1530 mm		2150x950 mm	
Thickness	plies	pcs/crate	plies	pcs/crate	plies	pcs/crate
4 mm	3-ply	135	3-ply	135		
5 mm	3-ply	108	3-ply	108		
6 mm	5-ply	90	5-ply	90		
8 mm	5-ply	67	5-ply	67		
9 mm	5-ply	60	5-ply	60		
10 mm	7-ply	54	7-ply	54		
12 mm	7-ply	43	7-ply	45		
15 mm	7-ply	35	7-ply	36		
18 mm	9-ply	28	9-ply	30		
22 mm	11-ply	23	11-ply	24		
25 mm	13-ply	21	13-ply	21		
30 mm	15-ply	18	15-ply	18		
35 mm	15-ply	15	15-ply	15		
40 mm	17-ply	13	17-ply	13	17-ply	13



The given information in this datasheet is non-binding and can be changed without prior notice